

Technical Specifications

Model S5080AP	DN154A
Processor & Speed	AMD Athlon XP2000+ 1.67GHz/266
Chipset	VIA KM266
Motherboard	Crossfire-GLA (MS-6390)
RAM	128/2700 MB 333DDR SDRAM (runs @ 266 MHz)
Maximum	2 GB (2x512MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 and 1024 MB DDR DIMMs
Free DIMM Sockets	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	128 KB L1, 256 KB L2 Integrated on Processor module
Hard Drive	40 GB
Optical Drive	DVD-ROM Drive: DVD (16x max.) / CD-ROM (48x max.)
Access Speed	DVD =115ms / CD-ROM =95ms
Transfer Speed	DVD = 21.6/sec. / CD-ROM = 7.2MB/sec.
Diskette Drive	3.5" (1.44MB)
Fax/Data Modem	V.92 56Kbps
Fax Speed	Up to 14.4Kbps
Data Compression	V.42 bis
Error Correction	V.42
EIA Fax Commands	Class 1
Video Graphics	AGP 4X Graphics
Controller	Integrated w/KM266 Chipset
Video Memory	UMA 32 MB
Network Card	10/100 BaseT, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650
Chassis	Chameleon, 250HV
USB Interface Specification	USB 2.0
External Ports	6= USB, 1= serial, 1= parallel
Front I/O Connector	2= USB
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	2= PCI, 1= AGP
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" internal
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

Copyright Hewlett-Packard Co. 1994-2003
This information is subject to change without notice and
is provided "as is" with no warranty.
Hewlett-Packard shall not be liable for any direct,
indirect, special, incidental or consequential damages
in connection with the use of this material.